



SHILOH
FLOORING

French Oak Engineered Hardwood Flooring

APPLICATION

Suitable for floors or walls

CONSTRUCTION

3.2mm Top Layer: Dry-Sawn White Oak

9.3mm Core: Hevea (Hevea brasiliensis)

1.5mm Back: Pine

SIZES

9/16" (14mm) x 7 1/2" x 72" RL (85% =72")

PACKING

22.46 SF/Carton - 40 Cartons/Pallet

T&G

T&G Standard

GRADE

Character

STAIN

8 Custom Stain Colors & Natural Available

EDGE

M84E - Slight 1mm

FINISH

UV Cured Urethane - Bona Kemi AB

INSTALLATION

Cleat, Staple, Glue, Floating - Radiant Heat Compatible

WARRANTY

30-Year Residential / 5-Year Light Commercial / Lifetime Structural

TESTS

Critical Radiant Flux: 0.51 w/cm² ASTM E 648-06 >

Class 1 NFPA Life Safety Code 101, IBC 804.2

Surface Burning: F110 - S 400 ASTM E84

Smoke Density: Average Dmc 463 Flaming - 512 Non Flaming ASTM E 662-05

Coefficient of Friction: .96 Dry Standard Neolite ASTM D 2394

Slip Resistance: W .86 D .85 ASTM CI 028

Moisture Content: >6% to 9% ASTM D 4442

Delamination test: ANSI/HPVA Bond Line Test 100% pass

CERTIFICATIONS

100% PEFC Pure Materials

100% FSC Certified Materials

California Prop 65 Certified

Lacey Act Compliant

Carb II Compliant

No added urea formaldehyde, halogenated hydrocarbons, herbicides, heavy metals

GREEN STATEMENT

Shiloh hardwood flooring may also contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems EQc4, as it uses adhesives that meet the SCAQMD rule #1168 and it contains no added urea-formaldehyde, as required by LEED®.

The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.